

# Model Documentation of the 'Perturbed linear cable mass problem of order 20'

## 1 Nomenclature

### 1.1 Nomenclature for Model Equations

- $x$  state vector
- $u$  control input vector
- $w$  noise vector
- $z$  regulated output vector
- $y$  measurement vector

## 2 Model Equations

State Vector and Input Vector:

$$x \in \mathbb{R}^{20} \quad u \in \mathbb{R}^1 \quad w \in \mathbb{R}^1 \quad z \in \mathbb{R}^3 \quad y \in \mathbb{R}^2$$

System Equations:

$$\dot{x}(t) = Ax(t) + B_1w(t) + Bu(t) \tag{1a}$$

$$z(t) = C_1x(t) + D_{11}w(t) + D_{12}u(t) \tag{1b}$$

$$y(t) = Cx(t) + D_{21}w(t) \tag{1c}$$

Outputs:  $z$



## 2.1 Exemplary parameter values

Symbol	Value					
A	0	0	0	0	0	0
	0	0	0	0	0	0
	0	0	0	0	0	0
	0	0	0	0	0	0
	0	0	0	0	0	0
	0	0	0	0	0	0
	0	0	0	0	0	0
	0	0	0	0	0	0
	0	0	0	0	0	0
	0	0	0	0	0	0
	0	0	0	0	0	0
	-91.1542732	64.6170927	-17.3140977	4.63929794	-1.2430941	0.333078454
	64.6170927	-108.468371	69.2563907	-18.5571918	4.97237639	-1.33231381
	-17.3140977	69.2563907	-109.711465	69.5894691	-18.6464115	4.9961768
	4.63929794	-18.5571918	69.5894691	-109.800685	69.6132695	-18.6523934
	-1.2430941	4.97237639	-18.6464115	69.6132695	-109.806667	69.6133968
	0.333078454	-1.33231381	4.9961768	-18.6523934	69.6133968	-10.0892197157
-0.0892197157	0.356878863	-1.33829574	4.99630408	-18.6469206	69.6133968	
0.0238004092	-0.0952016367	0.357006138	-1.33282291	4.97428552	-18.6469206	
-0.00598192102	0.0239276841	-0.0897288153	0.334987577	-1.25022149	4.63929794	
0.000127274915	-0.000509099661	0.00190912373	-0.00712739526	0.0266004573	-0.0892197157	
B	0					
	0					
	0					
	0					
	0					
	0					
	0					
	0					
	0					
	0					
	0					
	$-6.36374577 \cdot 10^{-6}$					
	$2.54549831 \cdot 10^{-5}$					
	$-9.54561865 \cdot 10^{-5}$					
	0.000356369763					
	-0.00133002287					
	0.0049637217					
-0.0185248639						
0.069135734						
-0.258018072						
0.962936555						
B <sub>1</sub>	0					
	0					
	0					
	0					
	0					
	0					
	0					
	0					
	0					
	0					
	0					
	$-6.36374577 \cdot 10^{-6}$					
	$2.54549831 \cdot 10^{-5}$					
	$-9.54561865 \cdot 10^{-5}$					
	0.000356369763					
	-0.00133002287					
	0.0049637217					
-0.0185248639						

### 3 Derivation and Explanation

This model is part of the "COMpleib" - library and was automatically imported into ACKREP.

The original description was:

CM1.IS Perturbed linear cable mass problem of order 20 J. A. Burns and B.B. King, "A reduced bases approach to the design of low order feedback controllers for nonlinear continuous systems", ICAM Virginia Polytechnic Institute and State University, Blacksburg Note CM1.IS instable version of CM1, i.e. A of CM1 is redefined by  $A=A+dA$ , where  $dA=[0 \ 0 \ 0 \ -ds*eye(0.5*nx)]$  such that the system matrix  $A=A+dA$  is not Hurwitz! Max. real part of  $eigA > 0$ ,  $sd=9.5825e-003$

### 4 Simulation




Figure 1: Simulation of the Perturbed linear cable mass problem of order 20.

### References

- [1] J. A. Burns and B.B. King, "A reduced bases approach to the design of low order feedback controllers for nonlinear continuous systems", ICAM Virginia Polytechnic Institute and State University, Blacksburg